



ISOTECHDESIGN.COM

1 800 476 2010

CASE STUDY FILE: CACI ISOLATOR C8, C4

CHEMOSPHERE

STERILITY TESTING ISOLATORS
WITH H2O2 DECONTAMINATION

CUSTOMER: FDA

APPLICATION:

cGMP sterility testing

FEATURES:

- C8 model 8' with 4 gloves and 2 antechambers for sterility testing.
- C4 model 4' with 2 gloves and 1 antechamber for compounding and transfer.
- Iso5 unidirectional airflow.
- Lift system
- 316 stainless steel with tempered glass.
- Inflatable seal.
- H2O2 decontamination and integration.
- Millipore sterility pump integration
- Alpha Beta doors
- Allen Bradley HMI/PLC



SPECIFICATIONS:

- H2O2 integration & faster decontamination cycle for both the C8 and C4
- Fast recovery rate.
- 1 PLC & HMI to control both the isolator and the H2O2 generator.
- H2O2 generator can decontaminate both the C8 and C4 units
- Turnkey solution: equipment integration, interfacing, start-up, training, validation (IQ/OQ/PQ) for full cGMP compliance.
- C4 is mobile for materials transfer.
- Safe for hazardous compounding with fully exhausted system in a BIBO filtration.

**Vertical unidirectional laminar airflow
(60 Feet/Min.@12 inches)**

**ALL TRANSFER CHAMBER DOORS MADE OF TEMPERED
GLASS WITH AN INFLATABLE GASKET.**

