

# CLEANFLOW™

Cost effective laminar flow hood solution for sterile compounding in an ISO 7 cleanroom  
USP <797> COMPLIANT



CleanFlow™

PROTECTING LIFE  
PROTÉGER LA VIE  
PROTEGIENDO LA VIDA



## CLEANFLOW™

## BENEFITS

**ASEPTIC**

**ISO Class 5 - Meets USP <797>**

**ERGONOMIC**

**Easy to operate, install and maintain**

**MODULAR**

**Many sizes available**

**ECONOMICAL**

**Cost effective clean air workstation**

### APPLICATIONS

#### FOR NON HAZARDOUS STERILE COMPOUNDING

#### AIR FILTRATION

- > **FILTER**                      HEPA filters (99.99% D O P at 0.3 µm) vertical
- > **AIRFLOW**                    Unidirectional
- > **FACE VELOCITY**            90 ft/min

#### FAN

- > Variable speed controller
- > On/Off switch

#### DIMENSION

| Mode  | Flow     | External Dimensions  | Internal Dimensions    |
|-------|----------|----------------------|------------------------|
| CAWS3 | Vertical | 39"W x 31.4"D x 49"H | 36"W x 25.6"D x 32"H   |
| CAWS4 | Vertical | 51"W x 31.4"D x 49"H | 48.4"W x 25.6"D x 32"H |
| CAWS6 | Vertical | 77"W x 26"D x 49"H   | 74"W x 25.6"D x 32"H   |

### MATERIALS OF CONSTRUCTION

- > Clear polycarbonate side panels and a white polypropylene back panel set into a sturdy anodized aluminium frame system
- > Stainless steel work surface and front panel

### NOISE LEVEL

- > Quiet, less than 65 dB

### LIGHTING

- > Compact fluorescent light fixture (40W)
- > On/Off switch

### ELECTRICAL REQUIREMENTS

- > 115V / 60 Hz / 1.25A

### ACCESSORIES

- > Painted adjustable, steel base frame with leveling casters
- > Stainless steel IV bar
- > Minihelic gauge
- > Passthrough
- > GFCI duplex
- > Adjustable front window (2 levels)

### DELIVERY

- > 4 weeks or immediate

### WARRANTY

- > 12 months

### DOCUMENTATION & SERVICES

- > Operation and maintenance manual
- > S.O.P. (Standard Operational Procedure)